



HIAB 477 EP-4 HiPro



Technical Data



The HIAB XS range



Version

HIAB 477 EP-4 HiPro

Lifting capacity	kNm	386
Lifting capacity	tm	39.4
Lifting capacity (ADC)	kNm	416
Lifting capacity (ADC)	tm	42.4
Outreach - lifting capacity, standard	m-kg	3.4 - 12,000 4.9 - 8,700 6.8 - 6,100 8.8 - 4,650 11.0 - 3,650 13.2 - 3,050
Outreach - lifting capacity, manual extensions	m-kg	
Hydraulic outreach, standard	m	13.2
Hydraulic boom extension	m	8.4
Outreach, manual extensions	m	0.0
Lifting height above installation level, hydr/man	m	15.9 / 0.0
Rec. oil flow	l/min	70 - 120
Power needed at rec. oil flow V80	kW	-
Power needed at rec. oil flow V91	kW	-
Working pressure	Mpa	35.0
Oil in tank	l	0 - 250
Tank capacity	l	0 - 0
Slewing angle	°	400 - 400
Max slope viable at full capacity	°	4
Slewing torque, gross	kNm	55.4
Slewing speed 80	°/s	12
Slewing speed	°/s	12
Lifting speed at standard hydraulic outreach	m/s	0.0
Height in folded position	mm	2,503
Width in folded position	mm	2,500
Install space required. Rotation area not included	mm	1,575
Install space required with hose and pipe kit	mm	1,705
Weight		
Crane in standard version without support legs	kg	4,160
Top seat	kg	0
Frame attachments	kg	117 - 117
Support leg equipment	kg	630 - 840

Data sheet

HIAB 477 EP-4 HiPro
